

MATERIAL SAFETY DATA SHEET



FREMONT INDUSTRIES, INC.
4400 Valley Industrial Blvd. N.
P.O. Box 67
Shakopee, MN 55379-1859

PHONE: (952) 445-4121
FAX: (952) 496-3027
EMERGENCY PHONE: (952) 445-4121
CHEMTREC: (800) 424-9300

FREMONT 9134

SECTION I GENERAL INFORMATION

NAME ON LABEL (Identity): FREMONT 9134 Inhibited Propylene Glycol
CHEMICAL FAMILY: Glycol
HMIS HAZARD CODES: Health (1) Flammability (1) Reactivity (0)
NFPA HAZARD CODES: Health (1) Flammability (1) Reactivity (0) Special Hazard: NA
HAZARD RATING SCALE: 4 = Severe 3 = Serious 2 = Moderate 1 = Slight 0 = Minimal

SECTION II HAZARDOUS INGREDIENTS

PRINCIPAL HAZARDOUS COMPOUNDS (CHEMICAL & COMMON NAME(S))	PERCENT (OPTIONAL)	OSHA PEL	ACGIH TLV	CAS #
Propylene Glycol	90-95	NE	NE	57-55-6

NA = Not Applicable NE = Not Established

SECTION III PHYSICAL DATA

BOILING POINT (°F): 370°F
VAPOR PRESSURE (mm Hg): 0.22 @ 20°C
SOLUBILITY IN WATER: Complete
VAPOR DENSITY (Air = 1): 2.62
APPEARANCE AND ODOR: Clear, yellow, odorless liquid.

SPECIFIC GRAVITY (H₂O = 1): 1.040
EVAPORATION RATE (BuAc = 1): NE
MELTING POINT (°F): NE

SECTION IV FIRE AND EXPLOSION HAZARD DATA

FLASH POINT (Method Used): 218°F (PMCC)
FLAMMABLE LIMITS: LEL: NE UEL: NE
EXTINGUISHING MEDIA: Water fog, alcohol foam, carbon dioxide, dry chemical.
AUTO-IGNITION TEMPERATURE: NE

SPECIAL FIRE FIGHTING PROCEDURES: Firefighters should wear all protective equipment including self-contained breathing apparatus when exposed to smoke, fumes or hazardous decomposition products. Keep containers cool with water-spray.

UNUSUAL FIRE AND EXPLOSION HAZARDS: None

SECTION V REACTIVITY DATA

STABILITY: Unstable Stable
CONDITIONS TO AVOID: None
INCOMPATIBILITY (Materials to Avoid): Strong oxidizers.
HAZARDOUS POLYMERIZATION: Will Not Occur May Occur
CONDITIONS TO AVOID: None
HAZARDOUS DECOMPOSITION PRODUCTS: Propionaldehyde, carbon monoxide in the presence of limited oxygen in a fire situation.

SECTION VI HEALTH HAZARD DATA

ROUTE(S) OF ENTRY: Inhalation, skin contact, eye contact.

HEALTH HAZARDS: Acute - May cause irritation to eyes, mucous membranes, and respiratory tract.
Chronic - Repeated excessive ingestion may cause central nervous system effects.

MATERIAL SAFETY DATA SHEET



FREMONT INDUSTRIES, INC.
4400 Valley Industrial Blvd. N.
P.O. Box 67
Shakopee, MN 55379-1859

PHONE: (952) 445-4121
FAX: (952) 496-3027
EMERGENCY PHONE: (952) 445-4121
CHEMTREC: (800) 424-9300

FREMONT 9134

SECTION VI HEALTH HAZARD DATA (continued)

CHEMICAL LISTED AS CARCINOGEN OR POTENTIAL CARCINOGEN: Yes ___ No X

NATIONAL TOXICOLOGY PROGRAM: Yes ___ No X

I.A.R.C. MONOGRAPHS: Yes ___ No X OSHA: Yes ___ No X

SIGNS AND SYMPTOMS OF EXPOSURE: Reddening, burning or itching of skin; watering or blurring of eyes; breathing difficulties.

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE: Respiratory or skin irritation; possible burns to eyes; breathing difficulties.

EMERGENCY AND FIRST AID PROCEDURES:

EYES: Flush immediately with cool water for 15 minutes. If any irritation persists, call physician.

SKIN: Flush immediately with cool water for 15 minutes. If any irritation persists, call physician.

INHALATION: Remove to fresh air. If any irritation persists, call physician.

INGESTION: DO NOT INDUCE VOMITING. If conscious, give 1-2 glasses of water. If any irritation persists, call physician and/or Chemtrec.

SECTION VII PRECAUTIONS FOR SAFE HANDLING AND USE

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Absorb bulk spill on inert material and containerize. Spill may be slippery. Wear all protective equipment.

WASTE DISPOSAL METHOD: Dispose of in accordance with federal, state, and local regulations.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING: Wear all protective equipment. Store away from and do not mix with oxidizing agents. Use with adequate ventilation.

OTHER PRECAUTIONS: Store at room temperature. Keep container closed when not in use.

SECTION VIII SPECIAL PROTECTION INFORMATION AND CONTROL MEASURES

RESPIRATORY PROTECTION (Specify Type): NIOSH/MSHA approved for dusts, fumes, and mists (TC-84A-0120; e.g. 3M #8210 or #8511 N-95 particulate respirator).

VENTILATION: LOCAL EXHAUST: Recommended
MECHANICAL (General): X SPECIAL: NA OTHER: NA

PROTECTIVE GLOVES: Rubber

EYE PROTECTION: Splash proof safety goggles or face shield.

OTHER PROTECTIVE CLOTHING OR EQUIPMENT: Full cover clothing, including long sleeves, rubber apron. Eye wash and safety shower in immediate vicinity.

WORK/HYGIENIC PRACTICES: Wear all protective equipment. Wash thoroughly after handling. Do not smoke near containers. Store away from food. Wash contaminated clothing before re-use.

MATERIAL SAFETY DATA SHEET



FREMONT INDUSTRIES, INC.
4400 Valley Industrial Blvd. N.
P.O. Box 67
Shakopee, MN 55379-1859

PHONE: (952) 445-4121
FAX: (952) 496-3027
EMERGENCY PHONE: (952) 445-4121
CHEMTREC: (800) 424-9300

FREMONT 9134

SECTION IX REGULATORY INFORMATION

CERCLA 40 CFR 302.4: NA

SARA TITLE III:

Section 302/304: NA
Section 311/312 Hazard Category: Acute
Section 313: NA

Bruce Busch (Chemist)

4/5/05

11/14/01

Prepared by (Optional)

Issue Date

Supersedes

We believe the information contained herein, including data, recommendations and other items set forth are reliable, but they are given without warranty of any kind, expressed or implied, as to the accuracy, completeness, dependability, or reliability thereof, except that such information is, to the best of Fremont's knowledge and belief, accurate as of the date indicated.