

18AG

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

Form Approved
OMB No. 44-R1387

MATERIAL SAFETY DATA SHEET

Required under USDL Safety and Health Regulations for Ship Repairing,
Shipbuilding, and Shipbreaking (29 CFR 1915, 1916, 1917)

SECTION I

MANUFACTURED for: LAWSON PRODUCTS, INC.		EMERGENCY TELEPHONE NO. (312) 694-9666
ADDRESS (Number, Street, City, State, and ZIP Code) 1666 East Touhy Avenue - Des. Plaines, Illinois 60018		
CHEMICAL NAME AND SYNONYMS		TRADE NAME AND SYNONYMS Electra-Klean
CHEMICAL FAMILY Pressurized Product	FORMULA TM 966C	

SECTION II - HAZARDOUS INGREDIENTS

PAINTS, PRESERVATIVES, & SOLVENTS	%	TLV (Units)	ALLOYS AND METALLIC COATINGS	%	TLV (Units)
PIGMENTS			BASE METAL		
CATALYST			ALLOYS		
VEHICLE			METALLIC COATINGS		
SOLVENTS			FILLER METAL PLUS COATING OR CORE FLUX		
ADDITIVES			OTHERS		
OTHERS					
HAZARDOUS MIXTURES OF OTHER LIQUIDS, SOLIDS, OR GASES				%	TLV (Units)
Methyl Chloroform				95	350ppm

SECTION III - PHYSICAL DATA

BOILING POINT (°F.)	N.A.	SPECIFIC GRAVITY (H ₂ O=1)	N.A.
VAPOR PRESSURE (mm Hg.)	Less than 130 @140°F	PERCENT, VOLATILE BY VOLUME (%)	100
VAPOR DENSITY (AIR=1)	Heavier than air	EVAPORATION RATE (_____ =1)	N.A.
SOLUBILITY IN WATER	Less than 1%		
APPEARANCE AND ODOR	Clear - Solvent		

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

FLASH POINT (Method used)	None	FLAMMABLE LIMITS	N.A.	LeI	UeI
EXTINGUISHING MEDIA	Waterfog, Foam CO ₂ or Dry Chemical				
SPECIAL FIRE FIGHTING PROCEDURES	Keep containers cool. Use equipment or shielding required to protect personnel against bursting or venting containers.				
UNUSUAL FIRE AND EXPLOSION HAZARDS	At elevated temperatures (130° or over) containers may vent, rupture, or burst.				