MATERIAL SAFETY DATA SHEET

This MSDS complies with OSHA'S Hazard Communication Standard 29 CFR 1910.1200 and OSHA Form 174

IDENTITY AND DISTRIBUTOR'S INFORMATION

NFPA Rating: Health-2; Flammability-3; Reactivity-0; Special-0	**HMIS Rating:** Health-2; Flammability-3; Reactivity-0; Personal Protection-B
Manufactured For: **Aftermarket Auto Parts Alliance, Inc.** Address: 14351 Blanco Road Address: San Antonio, TX 78216-7723	**DOT Hazard Classification:** ORM-D **Identity** (trade name as used on label): **PARTS MASTER PENETRATING LUBRICANT/PART #03931**
Phone: 210-492-4868	**MSDS Number: 393** **Revision- 8**
EMERGENCY RESPONSE NUMBER: 1-800-255-3924 **NOTICE: JUDGEMENT BASED ON INDIRECT TEST DATA**	Date Prepared: 03/16/99 **Prepared By: ES/KD/DL/CH** Information Calls: (770)422-2071

SECTION 1 - MATERIAL IDENTIFICATION AND INFORMATION

COMPONENTS-CHEMICAL NAMES AND COMMON NAMES (Hazardous Components 1% or greater; Carcinogens 0.1% or greater)	CAS Number	SARA III LIST	OSHA PEL (ppm)	ACGIH TLV (ppm)	Carcinogen Ref. Source **
ALIPHATIC PETROLEUM DISTILLATE	8052-41-3	No	100	100	d
2-BUTOXYETHANOL	111-76-2	No	50	25	d
PETROLEUM DISTILLATE	64742-53-6	No	5mg/M3	5mg/M3	d
ISOBUTANE / PROPANE BLEND	75-28-5	No	800	800	d
	74-98-6	No	1000	1000	d

SECTION 2 - PHYSICAL/CHEMICAL CHARACTERISTICS

Boiling Point: N/A	**Specific Gravity** (H_2O=1): Concentrate Only = .832
Vapor Pressure: PSIG @ 70°F (Aerosols): Max. 60	**Vapor Pressure** (Non-Aerosols)(mm Hg and Temperature): N/A
Vapor Density (Air = 1): N/E	**Evaporation Rate** (= 1): N/E
Solubility in Water: Insoluble	**Water Reactive:** No

Appearance and Odor: Light straw spray with aliphatic solvent odor.

SECTION 3 - FIRE AND EXPLOSION HAZARD DATA

FLAMMABILITY as per USA FLAME PROJECTION TEST (aerosols) **EXTREMELY FLAMMABLE**	Auto Ignition Temperature N/E	Flammability Limits in Air by % in Volume: % LEL: N/E % UEL: N/E

FLASH POINT AND METHOD USED (non-aerosols): N/A **SPECIAL FIRE FIGHTING PROCEDURES:** Self-contained breathing apparatus.	**EXTINGUISHER MEDIA:** Foam, dry chemical, carbon dioxide.

Unusual Fire & Explosion Hazards: Do not expose aerosols to temperatures above 130°F or the container may rupture.

SECTION 4 - REACTIVITY HAZARD DATA

STABILITY [X] STABLE [ ] UNSTABLE	**HAZARDOUS POLYMERIZATION** [ ] WILL [X] WILL NOT OCCUR
Incompatibility (Mat. to avoid): Strong oxidizing agents.	**Conditions to Avoid:** Open flame, welding arcs, heat, sparks.

Hazardous Decomposition Products: CO, CO_2, and various hydrocarbons.

SECTION 5 - HEALTH HAZARD DATA

PRIMARY ROUTES OF ENTRY: [X] INHALATION [ ] INGESTION [ ] SKIN ABSORPTION [ ] EYE [ ] NOT HAZARDOUS

ACUTE EFFECTS

Inhalation: Excessive inhalation of vapors can be harmful and may cause headache, dizziness, asphyxia, anesthetic effects and possible unconsciousness.

Eye Contact: Mild irritation.	**Skin Contact:** Mild irritation due to defatting of skin.

Ingestion: Possible chemical pneumonitis if aspirated into lungs. Nausea.

CHRONIC EFFECTS: (Effects due to excessive exposure to the raw materials of this mixture) **May cause elevated carboxyhemoglobin levels, eye damage, lung damage.**

Medical Conditions Generally Aggravated by Exposure: May aggravate existing eye, skin, or upper respiratory conditions.

EMERGENCY FIRST AID PROCEDURES

Eye Contact: Flush with water for 15 minutes. If irritated, seek medical attention.

Skin Contact: Wash with soap and water. If irritated, seek medical attention.

Inhalation: Remove to fresh air. Resuscitate if necessary. Get medical attention.

Ingestion: DO NOT INDUCE VOMITING. Drink two large glasses of water. Get immediate medical attention.

SECTION 6 - CONTROL AND PROTECTIVE MEASURES

Respiratory Protection (specify type): If vapor concentration exceeds TLV, use respirator approved by U.S. Bureau of Mines for organic vapor.

Protective Gloves: Neoprene, if skin easily irritated.	**Eye Protection:** Safety glasses recommended.

Ventilation Requirements: Adequate ventilation to keep vapor concentration below TLV.

Other Protective Clothing & Equipment: None

Hygienic Work Practices: Wash with soap and water before handling food. Remove contaminated clothing.

SECTION 7 - PRECAUTIONS FOR SAFE HANDLING AND USE

Steps To Be Taken If Material Is Spilled Or Released: Absorb with suitable medium. Incinerate or landfill according to local, state or federal regulations. DO NOT FLUSH TO SEWER.

Waste Disposal Methods: Aerosol cans when vented to atmospheric pressure through normal use, pose no disposal hazard.

Precautions To Be Taken In Handling & Storage: Do not puncture or incinerate containers. Do not store at temperatures above 130°F.

Other Precautions &/or Special Hazards: KEEP OUT OF REACH OF CHILDREN. Avoid food contamination. Remove ignition sources.

We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind.

** Chemical Listed as Carcinogen or Potential Carcinogen. [a] NTP [b] IARC Monograph [c] OSHA [d] Not Listed [e] Animal Data Only