

Material Safety Data Sheet



Revision Date: 03/02/2004

Issue date: 03/29/2004

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Product name:

High Strength Threadlocker Red Automotive Grade Item number:

27100

Product type:

Anaerobic Sealant

Company address:

Region:

United States

Henkel Corporation

Contact Information:

1001 Trout Brook Crossing

Telephone: 860.571.5100

Rocky Hill, Connecticut 06067

Emergency telephone: 860.571.5100

Internet: www.loctite.com

2. COMPOSITION/INFORMATION ON INGREDIENTS

<u>Hazardous components</u> Polyglycol dimethacrylate 25852-47-5	<u>%</u> 60-100	ACGIH TLV None	OSHA PEL None	OTHER None
Bisphenol A fumarate resin 39382-25-7	10-30	None	None	None
Saccharin 81-07-2	1-5	None	None	None
Cumene hydroperoxide 80-15-9	1-5	None	None	1 ppm (6 mg/m³) Skin (WEEL)

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

HMIS:

Physical state:

Liquid

Color: Odor:

Red

Mild

HEALTH:

FLAMMABILITY:

1* 1

PHYSICAL HAZARD:

1

Personal Protection:

See Section 8

WARNING:

CAUSES EYE IRRITATION.

MAY CAUSE ALLERGIC SKIN REACTION.

MAY CAUSE RESPIRATORY TRACT IRRITATION.

Relevant routes of exposure:

Skin, Inhalation, Eyes

Potential Health Effects

Inhalation:

May cause respiratory tract irritation.

Skin contact: Eye contact:

May cause allergic skin reaction. Contact with eyes will cause irritation.

Ingestion:

Not expected to be harmful by ingestion.

Existing conditions aggravated by

Eye, skin, and respiratory disorders.

exposure:

See Section 11 for additional toxicological information.

Item number: 27100

Product name: High Strength Threadlocker Red Automotive Grade 1 of 5

4. FIRST AID MEASURES

Inhalation:

Remove to fresh air. If symptoms develop and persist, get medical attention.

Skin contact:

Wash with soap and water. Remove contaminated clothing and shoes. Wash clothing before reuse.

Get medical attention if symptoms occur.

Eye contact:

Flush with copious amounts of water, preferably, lukewarm water for at least 15 minutes, holding

eyelids open all the time. Get medical attention.

Ingestion:

Do not induce vomiting. Keep individual calm. Obtain medical attention.

5. FIRE-FIGHTING MEASURES

Flash point:

Greater than 93°C (200°F) Tagliabue closed cup

Autoignition temperature:

Not available

Flammable/Explosive limits-lower %:

Not available

Flammable/Explosive limits-upper %:

Not available

Extinguishing media:

Foam, dry chemical or carbon dioxide.

Special fire fighting procedures:

None

Unusual fire or explosion hazards:

None

Hazardous combustion products:

Oxides of carbon. Oxides of sulfur. Oxides of nitrogen. Irritating organic vapors.

6. ACCIDENTAL RELEASE MEASURES

Environmental precautions:

Prevent product from entering drains or open waters.

Clean-up methods:

Soak up with inert absorbent. Store in a partly filled, closed container until disposal.

7. HANDLING AND STORAGE

Handling:

Avoid contact with eyes, skin and clothing. Avoid breathing vapor and mist. Wash thoroughly after

handling.

Storage:

For safe storage, store at or below 38°C (100°F). Keep in a cool, well ventilated area away from heat,

sparks and open flame. Keep container tightly closed until ready for use.

Incompatible products:

Refer to Section 10.

For information on product shelf life contact Henkel Customer Service at (800) 243-4874.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Engineering controls:

No specific ventilation requirements noted, but forced ventilation may still be required if concentrations exceed occupational exposure limts.

Respiratory protection:

Use NIOSH approved respirator if there is potential to exceed exposure limit(s).

Skin protection:

Use impermeable gloves and protective clothing as necessary to prevent skin contact. Neoprene

gloves. Butyl rubber gloves. Natural rubber gloves.

Eye/face protection:

Safety goggles or safety glasses with side shields.

Item number: 27100

Product name: High Strength Threadlocker Red Automotive Grade

See Section 2 for exposure limits.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state:

Liquid

Color:

Red

Odor:

Mild

Vapor pressure:

Less than 5 mm Hg at 27°C (80°F)

Not applicable

Boiling point/range: Melting point/range: Greater than 149°C (300°F)

Specific gravity:

Not available

Vapor density:

1.10

Evaporation rate:

Not available Not available

Solubility in water:

Slight

Partition coefficient (n-octanol/water):

Not available

VOC content:

12%; 132 grams/liter (EPA Method 24)

10. STABILITY AND REACTIVITY

Stability:

Stable.

Hazardous polymerization:

Will not occur.

Hazardous decomposition products:

Oxides of carbon. Oxides of sulfur. Oxides of nitrogen. Irritating organic vapors. Phenols.

Incompatability:

Strong oxidizers. Strong acids. Strong reducing agents. Copper. Iron. Rust.

Conditions to avoid:

See "Handling and Storage" (Section 7) and "Incompatabilty" (Section 10).

11. TOXICOLOGICAL INFORMATION

Product toxicity data:

Acute oral LD50 >5000mg/kg (rat)(estimated). Acute dermal LD50 greater than 2000 mg/kg (rabbit)

(estimated).

Carcinogen Status

Hazardous components	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen
Polyglycol dimethacrylate	No	No	No
Bisphenol A fumarate resin	No	No	No
Saccharin	No	No	No
Cumene hydroperoxide	No	No	No

Literature Referenced Target Organ & Other Health Effects

Hazardous components	Health Effects/Target Organs
Polyglycol dimethacrylate	Allergen, Irritant
Bisphenol A fumarate resin	Allergen, Irritant
Saccharin	No Target Organs
Cumene hydroperoxide	Allergen, Central nervous system, Corrosive, Irritant, Mutagen

12. ECOLOGICAL INFORMATION

Ecological information:

Not available

Item number: 27100

Product name: High Strength Threadlocker Red Automotive Grade

3 of 5

13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

Recommended method of disposal:

Dispose of according to Federal, State and local governmental regulations.

EPA hazardous waste number:

Not a RCRA hazardous waste.

14. TRANSPORT INFORMATION

U.S. Department of Transportation Ground (49 CFR):

Proper shipping name:

Unrestricted

Hazard class or division:

None

Identification number: Packing group:

None None

International Air Transportation (ICAO/IATA):

Proper shipping name:

Unrestricted

Hazard class or division:

None

Identification number: Packing group:

None None

WaterTransportation (IMO/IMDG):

Proper shipping name:

Unrestricted

Hazard class or division:

None

Identification number:

None

Packing group: Marine pollutant:

None None

United States Regulatory Information

TSCA 8 (b) Inventory Status:

TSCA 12 (b) Export Notification:

All components are listed or are exempt from listing on the Toxic Substances Control Act Inventory. None.

CERCLA/SARA Section 302 EHS:

CERCLA/SARA Section 311/312:

CERCLA/SARA 313:

None above reporting de minimus.

Immediate Health Hazard, Delayed Health Hazard

15. REGULATORY INFORMATION

This product contains the following toxic chemicals subject to the reporting requirements of section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 (40 CFR 372). Cumene

hydroperoxide (CAS# 80-15-9) .

California Proposition 65:

This product contains a chemical known to the State of California to cause cancer. o-Toluidine (CAS#

95-53-4).

Canada Regulatory Information

CEPA DSL/NDSL Status: WHMIS hazard class:

All components are listed on or are exempt from listing on the Domestic Substances List. D.2.A, D.2.B

16. OTHER INFORMATION

This material safety data sheet contains changes from the previous version in sections: Expanded chemical information in Section 2 and related sections.

Prepared by:

Kyra Kozak Woods, Health and Regulatory Affairs Specialist

DISCLAIMER: The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation does not assume responsibility for any results obtained by persons over whose methods Henkel Corporation has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any of Henkel Corporation's products. In light of the foregoing, Henkel Corporation specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel Corporation's products. Henkel Corporation further disclaims any liability for consequential or incidental damages of any kind, including lost profits.

Item number: 27100 Product name: High Strength Th