

**Section: 1 CHEMICAL PRODUCT AND COMPANY INFORMATION**

**Product Name:** Like90 Quick Check  
**Chemical Family:** Petroleum Distillates  
**Manufacturer:** Bonding Solutions, LLC  
3703 West Parkway Blvd.  
West Valley City, UT 84120 USA

**For Additional Product Information:** +1 888-954-5390  
**In Emergency:** +1 800-424-9300

**Section: 2 COMPOSITION/INFORMATION ON HAZARDOUS INGREDIENTS**

FOR EXPOSURE LIMITS SEE SECTION 8  
FOR OTHER TOXICOLOGICAL INFORMATION SEE SECTION 11

HAZARDOUS INGREDIENTS

Descriptive Name	CAS Number	Percentage Range	Hazard Type per CFR 1910.1200	Exposure Limits	LD <sub>50</sub>	LC <sub>50</sub>	NTP, IARC, Or OSHA Carcinogen
Petroleum Distillates	Mixture	95%	Combustible	Non Given	Oral: >8000 mg/kg	Not Determined	No
Carbon Dioxide	124-38-9	<5%	Not Hazardous	OSHA PEL 5000ppm ACGIH TLV 5000ppm	Not Determined	Not Determined	No

**Section: 3 HAZARDS IDENTIFICATION**

PHYSICAL HAZARDS:

**ACUTE HEALTH EFFECTS:** Breathing high concentrations may be harmful. Mist or vapor can irritate the throat and lungs. Breathing this material may cause central nervous system depression with symptoms including nausea, headache, dizziness, fatigue, drowsiness, or unconsciousness. Prolonged or repeated contact may dry the skin and cause irritation and burns.

**CHRONIC HEALTH EFFECTS:** Prolonged or repeated contact with the skin may dry the skin.

**IATA CLASSIFICATION:** Flammable according to IATA 3.2.5.2.a.

**FLAME PROJECTION TEST:** Flammable according to the flame projection test (IATA 3.2.5.2.a, ASTM D 3065, FSHA Sec. 1500.45)

HMIS RATINGS:

Health: 1  
Flammability: 2  
Reactivity: 0  
Protective Equipment: E

**Section: 4 FIRST AID MEASURES**

**EYES:** May be an eye irritant. Flush immediately with water for 15 minutes and take to physician.  
**SKIN:** Wash affected area and consult a physician if irritation persists.  
**INGESTION:** Call a physician and/or transport to emergency facility immediately. Do not induce vomiting so as to avoid aspiration of material into the lungs.  
**INHALATION:** Remove from exposure and restore breathing. Seek medical attention.

**Section: 5 FIRE AND EXPLOSION HAZARDS**

**FLAMMABILITY DATA:**

FLAMMABLE/COMBUSTIBLE/PYROPHORIC: Flammable  
FLASH POINT AND METHOD: 124° F (51° C) TCC  
AUTOIGNITION TEMPERATURE: Not established

**FLAMMABLE LIMITS AT NORMAL TEMPERATURE AND PRESSURE (PERCENT VOLUME IN AIR):**

LEL: 0.8% UEL: 6%

**EXPLOSION DATA:**

SENSITIVITY TO MECHANICAL IMPACT: Not Sensitive  
SENSITIVITY TO STATIC DISCHARGE: Not Sensitive

**EXTINGUISHING MEDIA:** Foam, Alcohol Foam, CO2, Dry Chemical, Water Fog

**FIRE FIGHTING TECHNIQUES AND COMMENTS:** Use standard firefighting techniques to fight fires involving this material

**HAZARDOUS COMBUSTION PRODUCTS:** Carbon dioxide, carbon monoxide, smoke, fumes, and/or unburned hydrocarbons.

**Section: 6 ACCIDENTAL SPILL/RELEASE INFORMATION**

FOR ALL TRANSPORTATION ACCIDENTS CALL CHEMTREC AT 1-800-424-9300.

**REPORTABLE QUANTITY:** Not Applicable

**SPILL MITIGATION PROCEDURES:**

Stop source of spill as soon as possible and notify appropriate personnel. Burn around spill area to prevent spill from spreading. Ventilate area. Do not flush into sewers.

**AIR RELEASE:**

Vapors may be suppressed by use of water fog or spray. Contain all liquid for treatment or neutralization.

**WATER RELEASE:**

Contain liquid for treatment.

**LAND SPILL:**

Create a trench to contain materials. Spilled materials may be contained using sand, clay, earth or a commercial absorbent. Do not place materials back in their original container.

**SPILL RESIDUES:**

Dispose of per guidelines under section 13, DISPOSAL CONSIDERATIONS.

**PERSONNEL PROTECTION FOR EMERGENCY SPILL AND FIRE FIGHTING SITUATIONS:**

Additional protective clothing must be worn to prevent personal contact with this material. Those items include but are not limited to gloves, apron, and safety glasses.

**Section: 7 HANDLING AND STORAGE**

DO NOT TAKE INTERNALLY. AVOID CONTACT WITH EYES AND CLOTHING. UPON CONTACT WITH SKIN OR EYES WASH OFF WITH WATER.

**STORAGE CONDITIONS:**

Store in a cool, dry, well-ventilated place.

STORE AT TEMPERATURES BELOW 120°F. DO NOT STORE OR USE NEAR HEAT, SPARKS, OR FLAMES. AVOID BREATHING VAPORS. VAPORS ARE HEAVIER THAN AIR AND WILL COLLECT IN LOW AREAS AND OTHER CONFINED AREAS.

**PRODUCT STABILITY AND COMPATIBILITY:**

SHELF LIFE LIMITATIONS: 36 months from date of shipment.  
INCOMPATIBLE MATERIALS FOR STORAGE OR TRANSPORT: None known.  
INCOMPATIBLE MATERIALS FOR PACKAGING: N/A

### Section: 8 PREVENTIVE MEASURES

#### PERSONAL PROTECTION FOR ROUTINE USE OF THIS PRODUCT:

**RESPIRATORY PROTECTION:** Breathing apparatus recommended only if necessary for application area used for application deems it necessary. Refer to NIOSH publication No. 89-105 and NIOSH No. 87-116. See OSHA requirement under 29 CFR 1910.1025 and 29 CFR 1910.134.  
**SKIN AND EYE PROTECTIVE EQUIPMENT:** Impervious gloves are recommended to prevent skin contact. Safety goggles to prevent eye contact are recommended.

#### ENGINEERING CONTROLS

**VENTILATION:** Local or mechanical to keep Section II ingredients below their exposure limits.

#### EQUIPMENT SPECIFICATIONS (WHEN APPLICABLE):

**RESPIRATOR TYPE:** None required  
**PROTECTIVE CLOTHING TYPE:** (This includes: gloves, boots, apron, protective suit):  
Impervious gloves, safety glasses

#### WASTE DISPOSAL:

Spilled material collected in absorbent material should be transferred to steel disposal or recovery drums. If this product becomes a waste, it DOES NOT meet the criteria of a hazardous waste as defined under 40 CFR 261, in that it does not exhibit the characteristics of hazardous waste under Subpart D. If this product becomes a waste, it should be disposed of in accordance with local, state and federal regulations by incineration.

### Section: 9 PHYSICAL AND CHEMICAL PROPERTIES

**PHYSICAL STATE(gas, liquid, solid):** Liquid  
**APPEARANCE:** Clear and colorless  
**ODOR:** Slight odor  
**FREEZING POINT:** Not Determined  
**BOILING RANGE:** 175° C- 195° C (347° F- 383° F)  
**DECOMPOSITION TEMPERATURE:** Not Determined  
**SPECIFIC GRAVITY (H2O=1):** 0.76  
**BULK DENSITY:** 6.3 lbs/gal @ 70° F  
**pH @ 25 Deg C:** Not Applicable  
**VAPOR PRESSURE @ 20 ° C:** 0.5 mm of Hg  
**SOLUBILITY IN WATER:** Slightly soluble (<0.1%)  
**VOLATILES, PERCENT BY WEIGHT:** 100%  
**EVAPORATION RATE:** <0.1 (n-Butyl acetate = 1.0)  
**VAPOR DENSITY:** Heavier than air  
**VOC CONTENT G/L:** 720 grams/Liter

### Section: 10 STABILITY AND REACTIVITY DATA

#### CONDITIONS UNDER WHICH THIS PRODUCT MAY BE UNSTABLE:

**MECHANICAL SHOCK OR IMPACT:** No  
**ELECTRICAL (STATIC) DISCHARGE:** No  
**HAZARDOUS POLYMERIZATION:** Will Not Occur  
**INCOMPATIBLE MATERIALS:** Strongly acids, alkalies, and oxidizers (liquid chlorine and oxygen).  
**CONDITIONS OF REACTIVITY:** None known  
**HAZARDOUS DECOMPOSITION PRODUCTS:** Carbon monoxide, carbon dioxide, smoke, fumes, and/or unburned hydrocarbons.

**Section: 11 TOXICOLOGICAL PROPERTIES**

ROUTES OF ABSORPTION

Skin contact. Inhalation.

WARNING STATEMENTS AND WARNING PROPERTIES:

DO NOT TAKE INTERNALLY.

SIGNS, SYMPTOMS AND EFFECTS OF EXPOSURE

INHALATION

ACUTE: Breathing high concentrations may be harmful. Mist or vapor can irritate the throat and lungs. Breathing this material may cause central nervous system depression with symptoms including nausea, headache, dizziness, fatigue, drowsiness, or unconsciousness.

SKIN

ACUTE: This product can cause mild, transient skin irritation with short-term exposure.  
CHRONIC: Repeated or prolonged skin contact can produce moderate irritation (dermatitis).

EYE

This product can cause transient mild eye irritation with short-term contact with liquid sprays or mists. Symptoms include stinging, watering, redness, and swelling.

INGESTION

If swallowed, this material can get into the lungs. This results in lung inflammation and other lung injury.

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE: Disorders of the following organs or organ systems that may be aggravated by significant exposure to this material or its components include:

Skin, lung

INTERACTIONS WITH OTHER CHEMICALS THAT ENHANCE TOXICITY: None known.

TARGET ORGAN TOXICITY: May cause damage to the following organs: kidney damage was observed in male rats. The mechanism by which this toxicity occurs is specific to the male rat and the kidney effects are not expected to occur in humans.

CHRONIC TARGET ORGAN TOXICITY: There are no known effects from repeated exposure.

REPRODUCTIVE AND DEVELOPMENTAL TOXICITY: There are no known or reported effects on reproductive function or fetal development.

CARCINOGENICITY: NTP? NO IARC MONOGRAPHS? NO OSHA REGULATED? NO

MUTAGENICITY: This product is not known to be mutagenic.

EXPOSURE LIMITS: Not Determined

**Section: 12 ECOLOGICAL INFORMATION**

AQUATIC TOXICITY: No data available.

**Section: 13 DISPOSAL CONSIDERATIONS**

Spilled material collected in absorbent material should be transferred to steel disposal or recovery drums.

If this product becomes a waste, it DOES NOT meet the criteria of a hazardous waste as defined under 40 CFR 261, in that it does not exhibit the characteristics of hazardous waste under Subpart D.

If this product becomes a waste, it should be disposed of in accordance with local, state and federal regulations by incineration.

**Section: 14 TRANSPORT INFORMATION**

DOT ROAD SHIPMENT (49CFR):	D.O.T. Non-Regulated (Aerosols)
OCEAN SHIPMENT (IMDG)	UN1950, Aerosols, flammable, 2.1 "Ltd Qty"
AIR SHIPMENT (IATA)	UN1950, Aerosols, flammable, 2.1 "Ltd Qty"
RQ:	None found in 49CFR 172.101 App A

**Section: 15 REGULATORY INFORMATION**

**INTERNATIONAL**

All components of this product are listed on the following inventories: MITI (Japan) EINECS (EEC) DSL (Canada).

**FEDERAL**

**TOXIC SUBSTANCES CONTROL ACT (TSCA):**

The components of this product are listed on the TSCA inventory.

**SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT TITLE III (SARA):**

**Section 302/304**

Requires emergency planning based on 'Threshold Planning Quantities' (TPQs), and release reporting based on Reportable Quantities (RQs) of 'Extremely Hazardous Substances' (EHS) listed in Appendix A of 40 CFR 355. There are no components of this material with known CAS numbers that are on the EHS list.

**Section 313**

This material does not contain chemicals with known CAS numbers subject to the reporting requirements of SARA Title III, Section 313 and 40 CFR 372:

**Comprehensive Environmental Response, Compensation, and Liability Act (CERCLA)**

This material does not contain chemical(s) with known CAS numbers classified as hazardous substances subject to the reporting requirements of CERCLA (40 CFR 302) and to the release reporting requirements of SARA (Section 302) based on reportable quantities (RQs):

**OSHA Regulations**

'Chemical-specific' U. S. Occupational Safety and Health Administration (OSHA) regulations (1910.1002 to 1910.1050) presented under 29 CFR 1910 do not apply to this material or its components.

**Other EPA Regulations**

No additional information available.

**State**

**California Safe Drinking Water and Toxic Enforcement Act of 1988- Proposition 65**

This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins under California Proposition 65 at levels that would be subject to the proposition

**California South Coast Air Quality Management District (SCAQMD) Rule 443.1 (VOC's)**

A Volatile Organic Compound (VOC) is any volatile compound of carbon excluding methane, carbon monoxide, carbonic acid, metallic carbides or carbonates, ammonium carbonate, 1,1,1-trichloroethane, methylene chloride, FC-23, CFC-113, CFC-12, CFC-11, CFC-22, CFC-114, and CFC-115. By this definition, this is a VOC material.

**Section: 16 PREPARATION INFORMATION**

REVISION INFORMATION: 1.1  
APPROVAL DATE: 05/06/2013  
SUPERSEDES: 1.0

This information is furnished without warranty, expressed or implied, except that it is accurate to the best knowledge of Bonding Solutions. The data in this sheet is related only to the specific material designated herein. Company assumes no legal responsibility for use or reliance upon these data.