

SAFETY DATA SHEET

RONSON BUTANE REFILL

1. IDENTIFICATION OF THE PREPARATION AND THE COMPANY

Product Name: Ronson Butane Refill
Synonyms, Trade Names: Butane Fuel 90ml to 400ml
Applications: Gas lighter fuel
Supplier: Ronson International Ltd.
International House, Old Brighton Road,
Lowfield Heath, Crawley, West Sussex. RH11 0QN
Emergency Telephone: 01293 843600 (office hours only)

2. COMPOSITION/INFORMATION ON INGREDIENTS

| Ingredient Name | CAS No | Contents | Health (class) | Risk (R No.) |
|-----------------------------|---|----------|----------------|--------------|
| Butane | 106 - 97 - 8 | 99% | | |
| Composition Comments | Substances indicating a hazard do so under EC Directives 88/379 & 67/548 Aerosol classified as Flammable | | | |

3. HAZARDS IDENTIFICATION

Flammable
Substances not indicating a health hazard may have Occupational Exposure Limits detailed in Section 8 of this data sheet
Ingredients are below the levels to cause the product to be classified

4. FIRST AID MEASURES

General: Note! Keep affected person away from heat, sparks and flames!
Eyes: Promptly wash eyes with water while lifting the eyelids. Get medical attention immediately. Continue to rinse. Burns should be flushed with water to normalise Temperature. Cover eyes with sterile dressing. Do NOT apply ointments or powder.
Skin: Remove affected person from source of contamination. Promptly stop exposure and get medical attention if frostbite has occurred. Promptly flush contaminated skin with soap or mild detergent and water. Promptly remove clothing if penetrated and flush the skin with water.
Inhalation: Move the exposed person to fresh air at once. Perform artificial respiration if breathing has stopped. When breathing is difficult, properly trained personnel may assist affected person by administering 100% oxygen. Keep the affected person warm and at rest. Get prompt medical attention
Ingestion: NEVER MAKE AN UNCONCIOUS PERSON VOMIT OR DRINK FLUIDS.
DO NOT induce vomiting Get medical attention immediately.

5. FIRE FIGHTING MEASURES

Extinguishing Media Stop flow of material to fire. Fire can be extinguished using foam, dry chemicals, and sand dolomite etc.
Special Fire Fighting Procedures
Use water to keep fire exposed cool and disperse vapours. Cool containers exposed to flames with water from side until well after fire is out. Move container from fire area if it can be done without risk.

SAFETY DATA SHEET

RONSON BUTANE REFILL

Unusual Fire & Explosion Hazards

Extremely flammable. May explode in a fire. May travel considerable distance to source of ignition and flashback.

Hazardous Decomposition Products

Toxic gases/vapours/fumes of carbon monoxide (CO), carbon dioxide (CO₂)

6. ACCIDENTAL RELEASE MEASURES

Spill Cleanup Methods

Extinguish all ignition sources. Avoid sparks, flames, heat and smoking. Ventilate, exhaust aerosol in well-ventilated area.

7. HANDLING AND STORAGE

Usage Precautions Keep away from heat, sparks and open flame

Storage Precautions Flammable/combustible. Keep away from oxidizers, heat and flames. May attack some plastics, rubber and coatings.

Storage Criteria Flammable compressed gas storage.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

| Ingredient Name: | CAS No. | STD | LT EXP (8 hrs) | ST EXP (15 min) |
|------------------|----------|-----|-------------------|--------------------|
| Butane | 106-97-8 | OES | 600 ppm | 750 ppm |

Ingredient comments Aerosol propellant

Protective Gloves Use protective gloves made of rubber (natural, latex)

Ventilation Well ventilated area

Respirators No specific recommendation made, but respiratory protection must be used
If the general level Occupational Exposure Level (OEL)

Eye Protection Under normal use should not be required. Always direct nozzle away from the face

Other Protection Use in well ventilated area

9. PHYSICAL AND CHEMICAL PROPERTIES

Colour colourless **Appearance** gas

Odour/taste mild (or faint), disagreeable

Physical Data Comments this product is an aerosol using hydrocarbon propellants. The flammability data is based on these hydrocarbons.

Solubility Description Slightly soluble in water

Specific Gravity (Water = 1) 0.599 @ 20°C **Mol Weight (At WT)** 58.14

SAFETY DATA SHEET

RONSON BUTANE REFILL

| | | | |
|---------------------------|--------------|--------------------------|-----------------|
| Vapour Pressure (mmHg) | 1520 @ 18°C | Vapour Density (air = 1) | 2.05 |
| Melting Point | -137 °C | | |
| Flash Point | -60 °C | Flash Point Method | CC (closed cup) |
| Auto ignition Temperature | 405 °C | | |
| Flammability Limit | lower % 1.90 | | |
| Flammability Limit | upper % 8.50 | | |

10. STABILITY AND REACTIVITY

| | |
|----------------------------------|---|
| Stability | Avoid heat, sparks and flames |
| Materials to avoid | Strong oxidizing agents |
| Conditions to avoid | Evaporates easily in air. Reacts strongly with oxidizers. |
| Hazardous Decomposition Products | Toxic gases/vapours/fumes of carbon monoxide (CO) carbon dioxide (CO ₂) |

11. TOXICOLOGICAL INFORMATION

| | |
|----------------------------------|---|
| Toxic Conc.-LC50 | 680 ppm/2h (inh - mus) |
| Target organs | Central nervous system, eyes, respiratory system and lungs |
| Health Warnings | Gas or vapour displaces oxygen available for breathing (asphyxiant). Narcotic effect |
| Medical Symptoms | May cause suffocation. Dizziness. |
| Acute and chronic health hazards | Contact with liquid form may cause frostbite. |

12. ECOLOGICAL INFORMATION

13. DISPOSAL CONSIDERATIONS

| | |
|------------------|---|
| Disposal Methods | Vent to atmosphere |
| Empty Containers | Dispose of empty containers without puncturing DO NOT INCINERATE |

14. TRANSPORT INFORMATION

ROAD:

| | | | |
|----------------------|------------------|---------------|-----|
| UN No | 1950 | Hazchem Code | 2WE |
| ADR Class | 2 | ADR Item No. | 3b |
| ADR Hazard No. | 23 Flammable Gas | | |
| CEFIC TEC ® No. | 276 | ADR Label No. | 3 |
| Label for conveyance | | | |

SAFETY DATA SHEET

RONSON BUTANE REFILL

AIR:

UN No. 1950 Air Transport Class No. 2
AIR Sub Class 3

SEA:

UN No. 1950 Sea Transport Class No. 2(2.1)

RAIL:

Rail Transport Class No 2 Road PT. 3b

15. REGULATORY INFORMATION

Label for Supply

Risk Phrases R 10 Flammable

Safety Phrases S - 9 Keep container in well ventilated place
S - 16 Keep away from sources of ignition - **NO SMOKING**
S - 33 Take precautionary measures against Static discharges

16. OTHER INFORMATION

-User Notes This product is supplied in an aerosol form using a highly flammable gas as a propellant. Properly used for the intended purpose and in accordance to this safety data sheet should not present any undue hazard.

Information Sources Dangerous Properties of Industrial Chemicals, 6.edition, N.Sax,1984
OSHA Air Contaminants - Permissible Exposure Limits (Title 29)
Handbook of Toxic and Hazardous Chemicals and Carcinogens, Sittig,'85
Hazardous Materials, Emergency Response Guidebook, DOT-P 5800.3, 1984
NIOSH/OSHA Pocket Guide to Chemical Hazards (latest edition)
Threshold Limit Values and Biological Exposure Indices for 1994 - 95
Chemical Safety Data Guide. Bureau of National Affairs , 1985

SDS No: 1001
Revision Date: May 2000
Revision No./Replaces: SDS issued 01 09 95
Revision Comments: New Safety Data to CHIP format