

MATERIAL SAFETY DATA SHEET

(Complies with OSHA Communication Standard 29 CFR 1910.1200 Dept. of Labor)

Identity: Electric Parts Cleaner, TM 2207 #89033 Dura Tron

Section I

MANUFACTURER'S NAME Curtis Industries A Congoleum Company	EMERGENCY TELEPHONE NO. (216) 951-2400 Ext. 5678
ADDRESS (Number, Street, City, State and ZIP Code) 34999 Curtis Boulevard, Eastlake, Ohio 44094	
INFORMATION TELEPHONE NO. (216) 951-2400 Ext. 282	

Date Prepared:

4/7/86

Signature of Preparer (optional)

Floyd D. Slanner

Section II—Hazardous Ingredients/Identity Information

Hazardous Components (Specific Chemical Identity: Common Name)	OSHA PEL	ACGIH TLV	Other Limits Recommended	% (opt)
Trichlorotrifluoroethane (76-13-1)		1000		40
Monofluorotrichloromethane (75-69-4)		1000		60

DOT SHIPPING—Consumer Commodity ORM-D

Section III—Physical/Chemical Characteristics

Boiling Point not applicable	75°F to 117°F	Specific Gravity (H ₂ O=1)	1.4
Vapor Pressure PSIG @ 70°F	100	Melting Point liquid	N.A.
Vapor Density (AIR=1) heavier than air	4.0	Evaporation Rate (Butyl Acetate=1)	6.0
Solubility in Water None			
Appearance and Color Clear—Ethereal odor			

Section IV—Fire and Explosion Hazard Data

Flash Point (Method Used) None	Flammable Limits	LEL None	UEL None
Extinguishing Media Use water fog, dry chemical or carbon dioxide			

75010

May 1985

MATERIAL SAFETY DATA SHEET

89034

Curtis Industries ————— A Congoleum Company
 34999 CURTIS BOULEVARD • EASTLAKE, OHIO 44094
EMERGENCY TELEPHONE NO. (216) 951-2400 Ext. 5678

PRODUCT CLASS (aerosol) Fluorocarbons DATE 4/1/82
 TRADE NAME Circuit Cooler. COLD SPOT # 89034 Lab No. 42790

Section II – HAZARDOUS INGREDIENTS

INGREDIENT	PERCENT	TLV		LEL	VAPOR PRESSURE
		PPM	mg/m ³		
Trichloromonofluoromethane	60	1000		None	
Dichlorodifluoromethane	40	1000		None	
Aerosol - Contents Under Pressure					40 ± 5 psig

Section III – PHYSICAL DATA

BILING RANGE Propellant below 0°F. VAPOR DENSITY HEAVIER LIGHTER THAN AIR
 VAPORATION RATE FASTER SLOWER THAN OTHER PERCENT VOLATILE BY WEIGHT 100 WEIGHT PER GALLON 3.3.
 *propellants

Section IV – FIRE AND EXPLOSION HAZARD DATA

COMBUSTIBILITY Consumer Commodity FLASH POINT None LEL None
 HAZARD CLASSIFICATION ORM-D-AIR
 EXTINGUISHING MEDIA Not Applicable
 USUAL FIRE AND EXPLOSION HAZARDS Keep at room temperature as exposure to direct sunlight or other heat may cause bursting. See back, Section VI, IX
 FIRE FIGHTING PROCEDURES Not Applicable

Identity: Electric Parts Cleaner, TM 2207 #89033 Dura Tron

Section I

MANUFACTURER'S NAME Curtis Industries	EMERGENCY TELEPHONE NO. (216) 951-2400 Ext. 5678
ADDRESS (Number, Street, City, State and ZIP Code) 34999 Curtis Boulevard, Eastlake, Ohio 44094	
INFORMATION TELEPHONE NO. (216) 951-2400 Ext. 28	

Date Prepared: 4/7/86
Signature of Preparer (optional) <i>Floyd J. Planner</i>

Section II—Hazardous Ingredients/Identity Information

Hazardous Components (Specific Chemical Identity: Common Name)	OSHA PEL	ACGIH TLV	Other Limits Recommended	%
Trichlorotrifluoroethane (76-13-1)		1000		40
Monofluorotrichloromethane (75-69-4)		1000		60

DOT SHIPPING—Consumer Commodity ORM-D

Section III—Physical/Chemical Characteristics

Boiling Point not applicable	75°F to 117°F	Specific Gravity (H ₂ O=1)	1.4
Vapor Pressure PSIG @ 70°F	100	Melting Point liquid	N.A.
Vapor Density (AIR=1) heavier than air	4.0	Evaporation Rate (Butyl Acetate=1)	6.0
Solubility in Water None			
Appearance and Color Clear-Etheral odor			

Section IV—Fire and Explosion Hazard Data

Flash Point (Method Used) None	Flammable Limits	LEL None	UEL None
Extinguishing Media Use water fog, dry chemical or carbon dioxide			