



MATERIAL SAFETY DATA SHEET

Lubegard[®] M-V Automatic Transmission Fluid Supplement

Section 1: PRODUCT AND COMPANY IDENTIFICATION

Product Name: Lubegard[®] M-V Automatic Transmission Fluid Supplement
Product Number: 62005, 62015, 62055
Product Use: Lubricant
Manufacturer/Supplier: International Lubricants, Inc.
P.O. Box 24743, Seattle WA 98124-0743, USA
Phone Number: (206) 762-5343
(800) 333-LUBE (5823)
Emergency Phone: CHEM TEL (800) 255-3924
CHEM TEL (813) 248-0585
Date of Preparation: December 16, 2011

Section 2: HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

WARNING:

MAY CAUSE EYE IRRITATION. MAY CAUSE SKIN IRRITATION. HARMFUL OR FATAL IF SWALLOWED.

Potential Health Effects: See Section 11 for more information.

Likely Routes of Exposure: Skin contact, skin absorption, eye contact, inhalation and ingestion.

Eye: May irritate eyes.

Skin: May irritate skin.

Ingestion: May cause stomach distress, nausea or vomiting. Harmful or fatal if swallowed.

Inhalation: Excessive intentional inhalation may cause respiratory tract irritation and central nervous system effects (headache, dizziness). Aspiration of material into lungs can cause chemical pneumonitis.

Chronic Effects: Prolonged or repeated exposure can cause drying, de-fatting and dermatitis.

Signs and Symptoms: Symptoms may include discomfort or pain, excess blinking and tear production, with marked redness and swelling of the conjunctiva. Symptoms may include redness, edema, drying, de-fatting and cracking of the skin.

Medical Conditions Aggravated By Exposure: Certain pre-existing conditions may make workers particularly susceptible to the effects of this chemical: asthma, allergies, impaired pulmonary function.

Target Organs: Not available.

Potential Environmental Effects: May cause long-term adverse effects in the aquatic environment. See Section 12 for more information.

Section 3: COMPOSITION / INFORMATION ON INGREDIENTS

Ingredient	CAS #	Wt. %
Oils, animal, mixed with vegetable oils, sulfurized	68991-19-5	5 - 10
Hydrotreated, heavy paraffinic petroleum distillate (severely hydrotreated)	64742-54-7	0.1 - 1



MATERIAL SAFETY DATA SHEET
Lubegard® M-V Automatic Transmission Fluid Supplement

Section 4: FIRST AID MEASURES

- Eye Contact:** In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. If easy to do, remove contact lenses, if worn. Get medical attention immediately.
- Skin Contact:** In case of contact, immediately flush skin with plenty of water. Remove contaminated clothing and shoes. Wash clothing before reuse. Call a physician if irritation develops and persists.
- Inhalation:** If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen.
- Ingestion:** If swallowed, do NOT induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person.
- General Advice:** In case of accident or if you feel unwell, seek medical advice immediately (show the label or MSDS where possible).
- Note to Physicians:** Symptoms may not appear immediately. .

Section 5: FIRE FIGHTING MEASURES

- Flammability:** Not flammable by WHMIS/OSHA criteria.
- Means of Extinction:**
- Suitable Extinguishing Media:** Powder, water spray, foam, carbon dioxide.
 - Unsuitable Extinguishing Media:** Not available.
- Products of Combustion:** Oxides of carbon.
- Explosion Data:**
- Sensitivity to Mechanical Impact:** Not available.
 - Sensitivity to Static Discharge:** Not available.
- Protection of Firefighters:** In case of fire and/or explosion do not breathe fumes. Firefighters should wear full protective clothing including self contained breathing apparatus.

Section 6: ACCIDENTAL RELEASE MEASURES

- Personal Precautions:** Use personal protection recommended in Section 8. Isolate area. Keep unnecessary personnel away.
- Environmental Precautions:** Prevent entry into waterways, sewers, basements or confined areas.
- Methods for Containment:** Prevent further leakage or spillage if safe to do so. Use sand, perlite or vermiculite as an absorbent for large spills of this material.
- Methods for Clean-Up:** Sweep up or gather material and place in appropriate container for disposal.
- Other Information:** Not available.

Section 7: HANDLING AND STORAGE

- Handling:**
Avoid contact with eyes. Avoid contact with skin. Do not swallow. Do not breathe vapor. Use only in a well-ventilated area. Handle and open container with care. When using do not eat or drink. Wash hands before breaks and immediately after handling the product.



MATERIAL SAFETY DATA SHEET

Lubegard® M-V Automatic Transmission Fluid Supplement

Storage:

Keep out of the reach of children. Store in a closed container away from incompatible materials. Store in a cool, dry, well-ventilated area. Keep container tightly closed. Keep away from food, drink and animal feedingstuffs.

Section 8: EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure Guidelines

Ingredient	Exposure Limits	
	OSHA-PEL	ACGIH-TLV
Oils, animal, mixed with vegetable oils, sulfurized	Not available.	Not available.
Hydrotreated, heavy paraffinic petroleum distillate (severely hydrotreated)	5 mg/m ³ (mist)	5 mg/m ³ (mist)

Engineering Controls: Provide adequate local exhaust ventilation to maintain worker exposure below exposure limits.

Personal Protective Equipment:

Eye/Face Protection: Wear safety glasses with side shields.

Hand Protection: Wear suitable gloves.

Skin and Body Protection: Wear suitable protective clothing.

Respiratory Protection: In case of insufficient ventilation, wear suitable respiratory equipment.

General Hygiene Considerations: Handle in accordance with good industrial hygiene and safety practice.

Section 9: PHYSICAL AND CHEMICAL PROPERTIES

Appearance:	Clear.
Color:	Dark red.
Odour:	Mild. Characteristic odor.
Odour Threshold:	Not available.
Physical State:	Liquid.
pH:	Not applicable.
Viscosity:	52.5 cSt @ 40 °C (104 °F)
Freezing Point:	Not available.
Boiling Point:	Not available.
Flash Point:	162 °C (324 °F)
Evaporation Rate:	Negligible.
Lower Flammability Limit:	Not available.
Upper Flammability Limit:	Not available.
Vapor Pressure:	Not available.
Vapor Density:	Not available.
Specific Gravity:	0.90
Solubility in Water:	Negligible.
Coefficient of Water/Oil Distribution:	Not available.



MATERIAL SAFETY DATA SHEET

Lubegard® M-V Automatic Transmission Fluid Supplement

Auto-ignition Temperature: Not available.
Percent Volatile, wt. %: Not available.
VOC content, wt. %: Not available.

Section 10: STABILITY AND REACTIVITY

Stability: Stable under recommended storage conditions.
Conditions of Reactivity: No dangerous reaction known under conditions of normal use.
Incompatible Materials: Acids. Oxidizers.
Hazardous Decomposition Products: Oxides of carbon.
Possibility of Hazardous Reactions: No dangerous reaction known under conditions of normal use.

Section 11: TOXICOLOGY INFORMATION

EFFECTS OF ACUTE EXPOSURE

Component Analysis

Ingredient	LD ₅₀ (oral)	LC ₅₀
Oils, animal, mixed with vegetable oils, sulfurized Hydrotreated, heavy paraffinic petroleum distillate (severely hydrotreated)	Not available. > 15 g/kg, rat	Not available. > 5.53 mg/L 4hr, rat.

Eye: May irritate eyes. Symptoms may include discomfort or pain, excess blinking and tear production, with marked redness and swelling of the conjunctiva.

Skin: May irritate skin. Symptoms may include redness, edema, drying, de-fatting and cracking of the skin.

Ingestion: Not a normal route of exposure. May cause stomach distress, nausea or vomiting. Harmful or fatal if swallowed.

Inhalation: May cause respiratory tract irritation. Aspiration of material into lungs can cause chemical pneumonitis.

EFFECTS OF CHRONIC EXPOSURE

Target Organs: Not available.

Chronic Effects: Not hazardous by WHMIS/OSHA criteria.

Carcinogenicity: Not hazardous by WHMIS/OSHA criteria.

Ingredient

Oils, animal, mixed with vegetable oils, sulfurized
Hydrotreated, heavy paraffinic petroleum distillate (severely
hydrotreated)

Chemical Listed as Carcinogen or Potential Carcinogen *

Not listed.

Not listed

* See Section 15 for more information.

Mutagenicity: Not hazardous by WHMIS/OSHA criteria.

Reproductive Effects: Not hazardous by WHMIS/OSHA criteria.

Developmental Effects:

Teratogenicity: Not hazardous by WHMIS/OSHA criteria.

Embryotoxicity: Not hazardous by WHMIS/OSHA criteria.



MATERIAL SAFETY DATA SHEET
Lubegard® M-V Automatic Transmission Fluid Supplement

Respiratory Sensitization: Not hazardous by WHMIS/OSHA criteria.

Skin Sensitization: Not hazardous by WHMIS/OSHA criteria.

Toxicologically Synergistic Materials: Not available.

Section 12: ECOLOGICAL INFORMATION

Ecotoxicity: May cause long-term adverse effects in the aquatic environment.

Persistence / Degradability: Not available.

Bioaccumulation / Accumulation: Not available.

Mobility in Environment: Not available.

Section 13: DISPOSAL CONSIDERATIONS

Disposal Instructions:

This material must be disposed of in accordance with all local, state, provincial, and federal regulations.

Section 14: TRANSPORTATION INFORMATION

DOT Classification:

Not regulated.

TDG Classification:

Not regulated.

Section 15: REGULATORY INFORMATION

Federal Regulations

Canadian: This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the MSDS contains all the information required by the Controlled Products Regulations.

US: MSDS prepared pursuant to the Hazard Communication Standard (CFR29 1910.1200).

SARA Title III

Ingredient	Section 302 (EHS) TPQ (lbs.)	Section 304 EHS RQ (lbs.)	CERCLA RQ (lbs.)	Section 313
Oils, animal, mixed with vegetable oils, sulfurized Hydrotreated, heavy paraffinic petroleum distillate (severely hydrotreated)	Not listed.	Not listed.	Not listed.	Not listed.
	Not listed.	Not listed.	Not listed.	Not listed.

State Regulations

California Proposition 65:

This product does not contain a chemical known to the State of California to cause cancer, birth defects or other reproductive harm.

Global Inventories

Ingredient	Canada DSL/NDSL	USA TSCA
Oils, animal, mixed with vegetable oils, sulfurized	DSL	Yes.
Hydrotreated, heavy paraffinic petroleum distillate (severely hydrotreated)	DSL	Yes.



MATERIAL SAFETY DATA SHEET

Lubegard® M-V Automatic Transmission Fluid Supplement

HMIS - Hazardous Materials Identification System

Health - 1 Flammability - 1 Physical Hazard - 0 PPE - B

NFPA - National Fire Protection Association:

Health - 1 Fire - 1 Reactivity - 0

Hazard Rating: 0 = minimal, 1 = slight, 2 = moderate, 3 = severe, 4 = extreme

WHMIS Classification:

Not controlled.

SOURCE AGENCY CARCINOGEN CLASSIFICATIONS:

OSHA (O) Occupational Safety and Health Administration.

ACGIH (G) American Conference of Governmental Industrial Hygienists.

A1 - Confirmed human carcinogen.

A2 - Suspected human carcinogen.

A3 - Animal carcinogen.

A4 - Not classifiable as a human carcinogen.

A5 - Not suspected as a human carcinogen.

IARC (I) International Agency for Research on Cancer.

1 - The agent (mixture) is carcinogenic to humans.

2A - The agent (mixture) is probably carcinogenic to humans; there is limited evidence of carcinogenicity in humans and sufficient evidence of carcinogenicity in experimental animals.

2B - The agent (mixture) is possibly carcinogenic to humans; there is limited evidence of carcinogenicity in humans in the absence of sufficient evidence of carcinogenicity in experimental animals.

3 - The agent (mixture, exposure circumstance) is not classifiable as to its carcinogenicity to humans.

4 - The agent (mixture, exposure circumstance) is probably not carcinogenic to humans.

NTP (N) National Toxicology Program.

1 - Known to be carcinogens.

2 - Reasonably anticipated to be carcinogens.

Section 16: OTHER INFORMATION

Disclaimer:

The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. It is the user's responsibility to satisfy oneself as to the suitability and completeness of this information for the user's own particular use.

Expiry Date: December 16, 2014

Revision #: 3.1

Prepared by: Nexreg Compliance Inc.

(519) 488-5126

www.nexreg.com