


MATERIAL SAFETY DATA SHEET

SECTION 1 - PRODUCT IDENTIFICATION AND USE	SECTION 6 - TOXICOLOGICAL PROPERTIES	Air Techniques Developer Code 0
MATERIAL IDENTIFIER Air Techniques Developer Code 0	ROUTE OF ENTRY SKIN CONTACT [X] SKIN ABSORPTION [X] EYE CONTACT [X] INHALATION ACUTE [X] INHALATION CHRONIC [X] INGESTION [X]	
MANUFACTURER'S NAME AIR TECHNIQUES INC.	EFFECTS OF ACUTE EXPOSURE TO MATERIAL	
STREET ADDRESS 70 CAMTIAQUE ROCK ROAD	EYE - May cause eye irritation. Hydroquinone in high concentrations may cause discoloration and opacity of the cornea.	
CITY HICKSVILLE	SKIN - May cause allergic skin reaction.	
STATE NY	INGESTION - Corrosion of tissue may occur with nausea, vomiting, and abdominal pain possible. Large doses of sulfite may cause circulatory disturbances and central nervous system depression and possible allergic reactions in some asthmatics.	
POSTAL CODE 11801	EFFECTS OF CHRONIC EXPOSURE TO MATERIAL None	
TELEPHONE NO. (516) 433-7676	SENSITIZATION PROPERTY [CARCINOGENICITY] None	REPRODUCTIVE EFFECTS [Possible Mutagen]
TELEPHONE NO.	STATEMENT OF PREVENTIVE MEASURES	IRRITANCY [Eye and skin possible]
HAZARDOUS INGREDIENTS	RESPIRATOR Use NIOSH approved cartridge respirator in poorly ventilated areas.	
HAZARDOUS INGREDIENTS	RESPIRATOR Use NIOSH approved cartridge respirator in poorly ventilated areas.	
Water	FOOTWEAR N/A	OTHER N/A
Sodium Sulfite	ENGINEERING CONTROLS Recommended ventilation - 10 room volumes per hour	
Potassium Hydroxide	LEAK AND SPILL PROCEDURE Neutralize with sodium bicarbonate, dike the spill and soak up with absorbent material. Put into plastic container for legal disposal.	
Potassium Carbonate	WASTE DISPOSAL Disposal must conform to Federal and Local Regulations. Consult local sewer authority.	
Hydroquinone	HANDLING PROCEDURES AND EQUIPMENT Store and handle in a tightly capped container. Wear protective gloves, clothes, and goggles. Keep work space uncluttered. Avoid contact with eyes and skin.	
N/A = Not Available	STORAGE REQUIREMENTS Do not store near food, drink, or tobacco products. Store in a well ventilated area. Store between 10 - 25 °C. Do not allow to freeze.	
SECTION 3 - PHYSICAL DATA	SPECIAL SHIPPING INFORMATION Ship above 4.4 °C. Protect from puncturing by handling or other equipment.	
ODOR AND APPEARANCE slight odor, light yellow color	SECTION 8 - FIRST AID MEASURES	
VAPOR PRESSURE N/A	EYES - Flush with water for at least 15 minutes. Get medical attention.	
VAPOR DENSITY N/A	SKIN - Remove contaminated clothing and wash skin thoroughly with non-alkaline type of cleanser. Wash clothes before re-use.	
PHYSICAL STATE GAS [] LIQUID [X] SOLID []	INHALATION - If symptomatic, remove to fresh air. If breathing becomes difficult, give oxygen. Get medical attention.	
EVAPORATION RATE N/A	INGESTION - If conscious, induce vomiting as directed by medical personnel. Give plenty of water. If not conscious, give artificial respiration. Obtain prompt medical attention.	
BOILING POINT (°C) > 100	SECTION 9 - PREPARATION OF MSDS	
FREEZING POINT (°C) 0	Form Preparation controlled by FILM PROCESSOR DEPARTMENT	TELEPHONE NO. (516) 433-7676
COEFF. WATER/OIL DIST N/A		DATE 1/15/02

SECTION 2 - HAZARDOUS INGREDIENTS	SECTION 4 - FIRE AND EXPLOSION DATA	SECTION 5 - REACTIVITY DATA
HAZARDOUS INGREDIENTS	FLAMMABILITY YES [] NO [X] IF YES, UNDER WHICH CONDITION	INCORPATABILITY WITH OTHER SUBSTANCES YES [X] NO [] IF YES, WHICH ONES Strong Acids
Water	[SPECIAL PROCEDURES Firefighters should wear self-contained breathing apparatus. Excessive heat may cause the production of hazardous decomposition products.]	REACTIVITY, AND UNDER WHAT CONDITIONS will neutralize acid and release some heat.
Sodium Sulfite	HAZARDOUS COMBUSTION PRODUCTS N/A	HAZARDOUS DECOMPOSITION PRODUCTS sulfur dioxide, carbon dioxide, possible carbon monoxide.
Potassium Hydroxide	EXPLOSION SENSITIVITY TO IMPACT DATA N/A	
Potassium Carbonate	EXPLOSION SENSITIVITY TO STATIC DISCHARGE N/A	
Hydroquinone	CHEMICAL STABILITY YES [X] NO [] IF NO, UNDER WHICH CONDITIONS	
N/A = Not Available		



6995-M

88