

Safety Data Sheet

Flowable Composite (Light Cure)

SDS DATE: 04/15/13

SECTION 1: PRODUCT AND COMPANY IDENTIFICATION

Product Name: Flowable Composite (Light Cure)

Other Names: S-CHEM-345-350, 393-396, 439-444, Flowable Composite in Shades A1, A2, A3, A3.5, B3, C3, B2, C2, D2, D3, A4, B1, B4, C1, C4, D4

Product Use: For the use in the construction of composites.

Supplier:

Company: Henry Schein, Inc.
135 Durea Road
Melville, NY 11747 USA
Henry Schein U.K. Holdings Ltd.
Gillingham ME8 OSB U.K.
Telephone: (800) 472-4346

Emergency Information Chemtrec:
(800) 424-9300

SECTION 2: HAZARDS IDENTIFICATION

Routes of Entry:

Inhalation, Skin contact, Eye contact, Ingestion

Potential Health Acute Effects:

Eyes:

Irritation to the eyes including but not limited to blurred vision, watering and discomfort.

Skin:

Repeated contact with skin may cause irritation or sensitization; allergic reactions to methacrylates may occur.

Inhalation:

Irritation may occur.

Ingestion:

Possible irritation. Seek medical attention immediately and report the amount ingested.

Potential Chronic Health Effects:

NE

Carcinogenicity:

Triethylene Glycol Dimethacrylate may contain trace amounts of substances known to the state of California to cause cancer and/or reproductive toxicity.

Ethoxylated Bisphenol A Dimethacrylate may contain trace amounts of ethylene oxide, which is listed as a carcinogen by IARC, NTP, OSHA and the state of California.

None of the other listed components are known carcinogens.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

COMPONENT:	CAS NO:	WT %:
Bisphenol "A" Diglycidyl Methacrylate	001565-94-2	10.0 – 20.0
Triethylene Glycol Dimethacrylate	109-16-0	1.0 – 10.0
Barium Glass	N/A	45.0 – 60.0
Silicon Dioxide	112945-52-5	1.0 – 10.0
Sodium Fluoride	7681-49-4	1.0 – 5.0
Dimethylamino Ethyl	2867-47-2	<1.0

Safety Data Sheet

Flowable Composite (Light Cure)

SDS DATE: 04/15/13

Ethoxylated Bisphenol A Dimethacrylate	41637-38-1	10.0 – 20.0
1,6 Hexanediol Dimethacrylate	6606-59-3	1.0 – 10.0
Silane, dichlorodimethyl- Reaction products with silica	68611-44-9	1.0 – 10.0

SECTION 4: FIRST AID MEASURES

Eyes:

Flush with copious amounts of water. Seek medical attention if symptoms persist.

Skin:

If irritation occurs and product is on the skin, rinse thoroughly with water, followed by a thorough washing of the affected area with soap and water. If irritation, redness or swelling persists, contact a physician immediately.

Ingestion:

If ingested, do not induce vomiting. If product has been swallowed, drink plenty of water or milk. If the patient is vomiting, continue to offer water or milk. Never give anything by mouth to an unconscious person. Provide an estimate of the time at which the material was ingested and the amount of the substance that was swallowed. Seek medical attention immediately.

Inhalation:

Immediately seek fresh air. Open windows and/or doors to increase ventilation. Seek medical attention if symptoms persist.

SECTION 5: FIRE-FIGHTING MEASURES

Flammable/Explosive Limits:

No Data

Flash Point:

No Data

Extinguishing Media:

Chemical Foam, CO₂, Dry Chemical Powder, Water Spray. NOTE: Water may be ineffective in extinguishing the fire.

Special Fire Fighting Measures:

Do not enter fire area without proper protection. Fight fire from a safe location. Wear SCBAs and full protective equipment.

Unusual Fire and Explosion Hazards:

Material may burn if exposed to flame. Use a water spray or fog to reduce or direct vapors.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Process for cleaning and take-up:

Evacuate the spill area. Maximize ventilation by opening doors and windows. Eliminate all sources of ignition. Use self-contained breathing apparatus and protective clothing, (e.g. goggles and gloves). Use non-sparking tools ONLY and dispose of the material in the proper closed container(s).

Wash all affected areas of the skin with warm water and soap. Remove clothing that has been contaminated and wash thoroughly.

Environmental Precautions:

Keep spills and cleaning runoffs out of sewers and open bodies of water. Spills on porous surfaces can contaminate the ground water. Dispose of in accordance with Federal, State and Local regulations, or appropriate governing standards.

SECTION 7: HANDLING AND STORAGE

Handling:

Handling advice:

To be handled by qualified dental professionals.

Follow instructions for use.

After each use, wash hands or exposed skin thoroughly. Do not smoke, eat or drink while using this product.

Fire and explosion protection:

Safety Data Sheet

Flowable Composite (Light Cure)

SDS DATE: 04/15/13

Store in a cool dry, at or below room temperature, place away from heat, sparks, flame, ultraviolet light and sunlight. Close container after each use.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure Guidelines:

COMPONENT:	CAS NO:	Exposure Limits in Air:	
		OSHA-PELs	ACGIH-TLVs
Bisphenol "A" Diglycidyl Methacrylate	001565-94-2	NE	NE
Triethylene Glycol Dimethacrylate	109-16-0	NE	NE
Barium Glass	N/A	0.5-20 mg/m ³ (component range, powder)	0.5-10 mg/m ³ (component range, powder)
Silicon Dioxide	112945-52-5	NE	NE
Sodium Fluoride	7681-49-4	2.5 mg/m ³	2.5 mg/m ³
Dimethylamino Ethyl	2867-47-2	NE	NE
Ethoxylated Bisphenol A Dimethacrylate	41637-38-1	NE	NE
1,6 Hexanediol Dimethacrylate	6606-59-3	NE	NE
Silane, dichlorodimethyl- Reaction products with silica	68611-44-9	15 mg/m ³ (total dust, powder)	NE

Engineering Controls:

Ventilation:

Professional: Follow precautions and directions on label.

Personal Protection:

Respiratory Protection:

A respirator should be worn whenever workplace conditions warrant its use. If necessary, use only respiratory protection authorized per U.S. OSHA's requirement in 29 CFR § 1910.134 or other appropriate governing standard.

Hand Protection:

Chemical resistant gloves should be worn when prolonged or repeated skin contact is expected. If necessary, refer to U.S. OSHA 29 CFR § 1910.138, or other appropriate governing standard. Eye wash stations, safety showers or sink basins are recommended.

Eye Protection:

Safety glasses or chemical splash goggles may be worn, if necessary refer to U.S. OSHA 29 § 1910.133 or other appropriate governing standard. Eye wash stations, safety showers or sink basins are recommended.

Other:

No special body protection is required; refer to appropriate governing standard(s).

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

General description:

State: Filled resin
Odor: Characteristic resin odor
Color(s): -----

Chemical Properties:

Designation:	Value:
Vapor Pressure	ND

Safety Data Sheet

Flowable Composite (Light Cure)

SDS DATE: 04/15/13

Boiling Point Freezing Point	ND
Solubility in Water	Insoluble
Viscosity	ND
Specific Gravity (H ₂ O = 1)	1.6 g/cc at 25°C/ 77°F
Percent Volatile W/W%	ND
Vapor Density (AIR = 1)	ND
Evaporation Rate (BuAc = 1)	ND

SECTION 10: STABILITY AND REACTIVITY

Stability:

This material is stable.

Reactivity:

Hazardous decomposition products:

Oxides of carbon when burned.

Incompatibility:

High temperatures, visible light sources, strong oxidizing agents. Keep away from sunlight and open flames.

Hazardous polymerization:

May occur in large quantities.

SECTION 11: TOXICOLOGICAL INFORMATION

Toxicity Data:

Bisphenol "A" Dimethacrylate:		
Oral (Rat)	LD ₅₀ :	3300 mg/kg
Oral (mouse)	LD ₅₀ :	2500 mg/kg
Oral (Rabbit)	LD ₅₀ :	2230 mg/kg
Intraperitoneal (Rabbit)	LD ₅₀ :	150 mg/kg
Dermal (Rabbit) 24-hour application	LD ₅₀ :	3600 mg/kg
Triethylene Glycol Dimethacrylate:		
Oral (Mouse)	LD ₅₀ :	10750 mg/kg
Oral (Rat)	LD ₅₀ :	10837 mg/kg
Silicon Dioxide:		
Intravenously (Rat)	LD ₅₀ :	500 mg/kg
Sodium Fluoride:		

Safety Data Sheet

Flowable Composite (Light Cure)

SDS DATE: 04/15/13

Oral (Rat)	LD ₅₀ :	52 mg/kg
Oral (Human)	LD ₅₀ :	71 mg/kg
Oral (Dog)	LD ₅₀ :	75 mg/kg
Oral (Rabbit)	LD ₅₀ :	200 mg/kg
Intraperitoneal (Dog)	LDL0:	50 mg/kg
Subcutaneous (Dog)	LDL0:	155 mg/kg

Dimethylamino Ethyl Methacrylate:		
Oral (Rat)	LD ₅₀ :	1550 mg/kg
Dermal (Rabbit)	LD ₅₀ :	>3000 mg/kg
Inhalation (Rat)	LD ₅₀ :	620 mg/kg/3-4h

Silane, dichlorodimethyl-		
Oral (Rat)	LD ₅₀ :	>5000 mg/kg
Inhalation (Rat) Acute	LD ₅₀ :	>0.477 mg/kg

SECTION 12: ECOLOGICAL INFORMATION

General ecological information:

Aquatic toxicity is possible, including physical damage or death to aquatic life; do not discharge into drains or the environment.

Bisphenol "A" Dimethacrylate:		
Menidia menidia	LC ₅₀ :	9.4 mg/L/96h
Selenastrum capicornutum (algae)	LC ₅₀ :	2.7 mg/L/96h
Pimephales promelas (Flathead minnow)	LC ₅₀ :	4.6 mg/L/96h
Skeletonema costatum (Diatom)	EC ₅₀ :	1.0 mg/L/96h
Mysidopsis bahi (Mysid)	LC ₅₀ :	1.1 mg/L/96h
Daphnia magna (Water flea)	EC ₅₀ :	10200 µg/L/96h
Americamysis bahia (Opossum shrimp)	LC ₅₀ :	1100µg/L/96h
Mysidopsis bahia (Mysid shrimp, 6d old)	LC ₅₀ :	1.1 mg/L/96h
Oryzias latipes (Medaka, high-eyes-ad.female)	LC ₅₀ :	8300 µg/L/72h
Oryzias latipes (Medaka, high-eyes, eggs) Inhibition of hatching	IC ₅₀ :	9.0 mg/L/96h
Hydra vulgaris	LC ₅₀ :	6.9 mg/L/96h
Acartia tonsa (copepod 10-12 d. old)	LC ₅₀ :	3.4 – 5.0 mg/L/48h
Xiphophorus helleri (Swordfish Tail)	LC ₅₀ :	17.93 mg/L/96h
Oncorhynchus mykiss (Rainbow Trout)	LC ₅₀ :	3 – 5 mg/L/96h
Brachydanio rerio	LC ₅₀ :	9.9 mg/L/96h
Cyprinodon variegates (Sheepshead)	LC ₅₀ :	7.5 mg/L/96h

Safety Data Sheet
Flowable Composite (Light Cure)

SDS DATE: 04/15/13

minnow)		
Acartia tonsa (copepod) Affected larval development rate	EC ₅₀ :	0.88 mg/L/5 days

Silane, dichlorodimethyl-		
Brachydanio rerio	LC ₅₀ :	>10000mg/L/96h
Daphnia magna	EC ₅₀ :	>10000 mg/L/24h
Scenedesmus subspicatus	IC ₅₀ :	>10000 mg/L/72h

Sodium fluoride:		
Chlorella vulgaris (Green algae)	LC ₅₀ :	7000 uM/L/72h
Ceriodaphnia dubia (Water flea)	EC ₅₀ :	352 mg/L /24h
Cyprinodon variegatus	LC ₅₀ :	> 500000 ug/L/96h
Lepomis macrochirus (Bluegill);	LC ₅₀ :	830 ppm/L/96h
Oncorhynchus mykiss (Rainbow trout);	LC ₅₀ :	317 ppm/L/ 96h
Pimephales promelas (Fathead minnow);	LC ₅₀ :	180000 ug/L /96h

Silicon Dioxide:		
Brachydanio rerio	LC ₅₀ :	>10000mg/L/96h
Daphnia magna	EC ₅₀ :	>10000 mg/L/24h

No other components of this product were found to cause ecotoxicity.

SECTION 13: DISPOSAL CONSIDERATIONS

Waste disposal of product:

Collect spilled material. Place in closed container. Dispose of waste at an appropriate waste disposal facility according to current applicable laws and regulations.

Contaminated substrates may be RCRA/OSHA hazardous waste due to the potential for heat generation. Reference codes 40 CFR §261 and 29 CFR § 1910, or the appropriate governing agencies rules and regulations.

SECTION 14: TRANSPORT INFORMATION

Not classified as a dangerous good

SECTION 15: REGULATORY INFORMATION

Symbols of Danger:

St. Andrews Cross
Xi- Irritant
Contains methacrylic ester.

R-Phrase:

R36/38 – Irritating to eyes and skin.

S-Phrase:

S26/27/28 – Avoid contact with skin and eyes. In case of contact with eyes rinse immediately with plenty of water and seek medical attention. After skin contact, wash area immediately with plenty of soap and water.
S29- Do not empty into drains.

Safety Data Sheet

Flowable Composite (Light Cure)

SDS DATE: 04/15/13

S37/39- Wear suitable gloves and eye/face protection.

SECTION 16: OTHER INFORMATION

All information, recommendations, and suggestions appearing herein concerning our product are based upon tests and data believed to be reliable. However, it is the user's responsibility to determine the safety, toxicity, and suitability for his own use of the product described herein. Since the actual use by others is beyond our control, no guarantee, express or implied, is being made as to the effects of such use, the results obtained, or the safety and toxicity of the product nor is there any assumed liability arising out of use, by others, of the product referred to herein. The information herein is not to be construed as absolutely complete since additional information may be necessary or desirable when particular or exceptional conditions or circumstances exist or because of applicable laws or government regulations.

