

MATERIAL SAFETY DATA SHEET

SECTION 1 - SOURCE/IDENTITY/USE INFORMATION

MANUFACTURER	SUPPLIER
GC AMERICA INC.	
3737 West 127th St.	
Alsip, Illinois, 60658	
Telephone: 708-597-0900	
Hours: Mon.- Fri. 8:00 am. - 5:00 pm. C.S.T.	
Transportation Emergency Telephone No. 800-424-9300	

COMMON NAME: FUJI PLUS LIQUID
 FUJI PLUS CAPSULE LIQUID
 FUJI PLUS EWT

Chemical Name: N.A.

PRODUCT USE: Reinforced glass ionomer cement - Liquid component

The following information is provided with regard to the toxicity and hazards of the pure components present in this portion of the unmixed powder/liquid system.

=====

SECTION 2 - HAZARDOUS INGREDIENTS/IDENTITY INFORMATION

COMPONENT AND C.A.S.	EXPOSURE LIMITS	LD50/LC50	%
Polyacrylic acid (not listed)	TWA=10ppm (ACGIH)	LD50 = 2500mg/kg (oral rat) LC50 = N.E.	22-24%
2-Hydroxyethyl methacrylate 868-77-9	N.E.	LD50=5888mg/Kg (oral rat) LC50=N.E.	35-40%
Di-2-Methacryloxyethy- 2,2,4, Trimethyl hexamethylene dicarbamate (not listed)	N.E.	N.E.	5-7%
Tartaric Acid 87-69-4	N.E.	N.E.	5-7%

=====

SECTION 8 - CONTROL MEASURES - continued

OTHER PROTECTIVE CLOTHING OR EQUIPMENT: Do not spill on clothing.
yewash station

WORK/HYGIENIC PRACTICE: N.E.

=====

SECTION 9- PREPARATION INFORMATION

This data is supplied to comply with OSHA Hazard Communication Standard 29 CFR 1910,1200 and W.H.M.I.S. CPR

PREPARED BY: T. Joritz
Director Regulatory Affairs

Date: 03 January 2000

=====

N.A. = NOT APPLICABLE
N.E. = NOT ESTABLISHED

The information herein is given in good faith but no warranty expressed or implied is made.

NFPA

FIRE 1 TOXICITY 1 REACTIVITY 0 SPECIAL ACID

=====