

PHIPPS PRODUCTS CORP -- LUBRICATING OIL,GENERAL PURPOSE -- 9150-00-273-2389

=====
Product Identification
=====

Product ID:LUBRICATING OIL,GENERAL PURPOSE

MSDS Date:10/14/1997

FSC:9150

NIIN:00-273-2389

MSDS Number: CFKQY

=== Responsible Party ===

Company Name:PHIPPS PRODUCTS CORP

Address:OUT OF BUSINESS

City:BOSTON

State:MA

ZIP:02111

Country:US

Info Phone Num:804-279-4371 (HMIS HELP LINE)

Emergency Phone Num:OUT OF BUSINESS

Preparer's Name:DSCR-VBA (HMIS)

CAGE:86511

=== Contractor Identification ===

Company Name:PHIPPS PRODUCTS CORP

Address:186 LINCOLN ST SUITE 502

Box:City:BOSTON

State:MA

ZIP:02111-2403

Country:US

Phone:OUT OF BUSINESS

CAGE:86511

=====
Composition/Information on Ingredients
=====

Ingred Name:PETROLEUM BASE OIL

Other REC Limits:NONE RECOMMENDED

Ingred Name:ADDITIVES

Other REC Limits:NONE RECOMMENDED

=====
Hazards Identification
=====

LD50 LC50 Mixture:LD50 (ORAL, RAT) IS UNKNOWN.

Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO

Reports of Carcinogenicity:NTP:UNKNOWN IARC:UNKNOWN OSHA:NO

Health Hazards Acute and Chronic:TARGET ORGANS:EYE, SKIN, RESPIRATORY & GI TRACTS. ACUTE- EYE:MAY CAUSE IRRITATION. SKIN:PROLONGED CONTACT MAY CAUSE IRRITATION, DERMATITIS. INHALE:HIGH VAPOR/MIST CONCENTRATIONS MAY CAUSE DROWSINESS & IRRITATION. ORAL:MAY CAUSE ABDOMINAL DISCOMFORT, VOMITING. ASPIRATION HAZARD. CHRONIC-UNKNOWN.

Explanation of Carcinogenicity:USED OIL HAS SHOWN TO CAUSE SKIN CANCER IN LABORATORY ANIMALS.

Effects of Overexposure:IRRITATION, NAUSEA, HEADACHE, DIZZINESS, DROWSINESS, VOMITING

=====
First Aid Measures
=====

First Aid:GET MEDICAL HELP IF SYMPTOMS PERSIST. INHALED:MOVE TO FRESH AIR. PROVIDE CPR/OXYGEN IF NEEDED. EYES:IMMEDIATELY FLUSH WITH

WATER FOR 15 MINUTES. HOLD EYELIDS OPEN. SKIN:WASH WITH SOAP & WATER. ORAL:SEEK MEDICAL ATTENTION. IF VOMITING OCCURS, KEEP HEAD BELOW HIPS. DO NOT GIVE ANYTHING BY MOUTH TO AN UNCONSCIOUS PERSON.

=====
===== Fire Fighting Measures =====

Flash Point Method:COC
Flash Point:>275F,>135C
Extinguishing Media:USE FOAM, CARBON DIOXIDE, DRY CHEMICAL. WATER OR FOAM MAY CAUSE FROTHING.
Fire Fighting Procedures:WEAR FIRE FIGHTING PROTECTIVE EQUIPMENT AND NIOSH-APPROVED SELF CONTAINED BREATHING APPARATUS. COOL FIRE EXPOSED CONTAINERS WITH WATER SPRAY.

=====
===== Accidental Release Measures =====

Spill Release Procedures:WEAR PROTECTIVE EQUIPMENT. PROVIDE ADEQUATE VENTILATION. REMOVE SPILL WITH INERT ABOBENT SUCH AS SAND, CLAY, EARTH. TRANSFER TO PROPER CONTAINERS FOR DISPOSAL. PREVENT RUN-OFF TO ENTER SEWERS OR WATE RWAYS. REPORT SPILLS AS REQUIRED TO AUTHORITIES.
Neutralizing Agent:NOT RELEVANT

=====
===== Handling and Storage =====

Handling and Storage Precautions:STORE AWAY FROM HIGH HEAT. KEEP CONTAINERS CLOSED WHEN NOT IN USE. KEEP OUT OF REACH OF CHILDREN.
Other Precautions:DO NOT GET IN EYES, ON SKIN OR ON CLOTHING. WASH THOROUGHLY AFTER HANDLING. AVOID BREATHING OIL MIST. DISCARD LUBRICANT-SOAKED SHOES. REMOVE LUBRICANT-SOAKED CLOTHING AND LAUNDER BEFORE RE-USE.

=====
===== Exposure Controls/Personal Protection =====

Respiratory Protection:NONE NORMALLY NEEDED. IF WORKING IN CONFINED AREAS, IF EXCESSIVE MISTING IS EXPECTED OR IF EXPOSURE MAY OR DOES EXCEED RECOMMENDED PERMISSIBLE EXPOSURE LIMITS, WEAR NIOSH-APPROVED ORGANIC VAPOR AND MI ST RESPIRATOR (REFER TO 29 CFR 1910.134)
Ventilation:USE ADEQUATE VENTILATION TO KEEP OIL MISTS OF THIS MATERIAL BELOW APPLICABLE STANDARD(S).
Protective Gloves:NITRILE/NEOPRENE FOR REPEATED CONTACT
Eye Protection:SAFETY GLASSES, FACE SHIELD RECOMMENDED
Other Protective Equipment:EYE WASH STATION AND SAFETY SHOWER. INDUSTRIAL-TYPE WORK CLOTHING AND APRON AS REQUIRED.
Work Hygienic Practices:OBSERVE GOOD PERSONAL HYGIENE PRACTICES AND RECOMMENDED PROCEDURES.
Supplemental Safety and Health
NO MSDS WAS AVAILABLE FROM MANUFACTURER. THIS MSDS WAS PREPARED BY THE PROFESSIONAL OF DSCR-VBA/HMIS. THE USER'S RESPONSIBILITY IS TO GATHER INFORMATION AND USE THE MATERIAL PROPERLY TO PROTECT EMPLOYEES AND ENVIRONMENT.

=====
===== Physical/Chemical Properties =====

HCC:V6
NRC/State Lic Num:NOT RELEVANT
Vapor Density:>1
Spec Gravity:<1
Solubility in Water:NEGLIGIBLE
Appearance and Odor:OIL

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid: YES
Stability Condition to Avoid: EXCESSIVE HEAT
Hazardous Decomposition Products: MAY PRODUCE SMOKE, CARBON MONOXIDE,
CARBON DIOXIDE AND OTHER UNIDENTIFIED COMPOUNDS.

===== Disposal Considerations =====

Waste Disposal Methods: DISPOSE OF WASTE IN COMPLIANCE WITH APPLICABLE
LOCAL, STATE AND FEDERAL LAWS AND REGULATIONS. RCRA EMERGENCY
NUMBER: 800-424-9346. DO NOT CONTAMINATE ANY LAKES, STREAMS, PONDS
OR UNDERGROUND WATER SUPPLY. INCINERATION IS RECOMMENDED.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.